

COOLING SUPPLIES

REFRIGERANT R600a ISOBUTANE

Material Safety Data Sheet

Date Prepared: 19/09/2017

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ISOBUTANE

CHEMICAL FAMILY: Paraffin Series Hydrocarbon

DISTRIBUTOR INFORMATION:

ILYS Ltd t/a Cooling Supplies

11A King St

Rangiora

New Zealand

Ph: 0274 746 786

Fax: 03 313 7631

EMERGENCY TELEPHONE NUMBER 0800 746 786 (NZ only)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components:

Material	CAS Number	%
LIQUIFIED PETROLEUM GAS	75-28-5	100

3. HAZARDS IDENTIFICATION

Potential Health Effects

INGESTION: Aspiration Hazard!

INHALATION: Inhalation of vapor may produce anesthetic effects and feeling of euphoria. Prolonged overexposure can cause rapid breathing, headache, dizziness, narcosis, unconsciousness, and death from asphyxiation, depending on concentration and time of exposure.

SKIN CONTACT: Contact with evaporating liquid can cause frostbite.

EYE CONTACT: Liquid can cause severe irritation, redness, tearing, blurred vision, and possible freeze burns.

4. FIRST AID MEASURES

INHALATION

Remove to fresh air. If breathing has stopped, restore breathing at once. Administer oxygen and get medical help.

SKIN CONTACT

For liquid contact, warm areas gradually and get medical attention if there is evidence of tissue damage. Flush area with plenty of water.

EYE CONTACT

For liquid contact, irrigate with running water for minimum of 15 minutes. Consult physician immediately if frostbite occurs.

INGESTION

Do not induce vomiting. Contact a physician immediately.

5. FIRE FIGHTING MEASURES

Flammable Properties

FLASH POINT (METHOD): -117 F (Open Cup)

UPPER EXPLOSIVE LIMIT (vol.) gas in air): 8.4%

LOWER EXPLOSIVE LIMIT (vol.) gas in air): 1.8%

EXTINGUISHING MEDIA:

Dry Chemical Extinguisher (B-C), Water

SPECIAL FIRE FIGHTING PROCEDURES:

Stop the release of materials if possible. Cool the vapour space of the storage container with water spray. Avoid accumulation of unburned materials. Remove personnel in general area. Observe maximum isolation when extinguishing fire. Expansion of liquid and change of state from liquid to vapour will allow combustible mixture to encompass a large area.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Vapours are heavier than air and may travel along the ground or may be moved by ventilation systems and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Avoid sources of ignition-Ventilate area. Use water fog to evaporate or ventilate. Protect body against contact with liquid. If confined space – Use self-contained breathing apparatus. Consult local fire authorities.

7. HANDLING AND STORAGE

Comply with state and local regulations covering liquefied petroleum gases.

Comply with NFPA Pamphlet #58.

Store small containers in well-ventilated areas, away from heat or sources of ignition. Prohibit smoking in areas of storage or use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION:

Mechanical: Provide as needed to keep concentration in air below TLV and LEL

Local Exhaust: Continuous ventilation recommended

Special: Explosion proof fans and motors

RESPIRATORY PROTECTION: NIOSH approved self-contained breathing apparatus

PROTECTIVE GLOVES: Impervious, insulated gloves recommended

EYE PROTECTION: Face shield or goggles recommended

OTHER: Impervious clothing for prolonged or repeated contact

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Data

ODOUR & APPEARANCE: Clear, Colourless liquefied gas with sweet petroleum odour

SOLUBILITY IN WATER: @ 21 Deg. C: 0.008%

SPECIFIC GRAVITY (H₂O=1.00): 0.564

BOILING RANGE: 10.9 Deg. F

PRESENT VOLATILE BY VOLUME: 100%

VAPOUR PRESSURE @ 21 Deg. C: 31 psig

VAPOUR DENSITY (air = 1.00): 2.006

EVAPORATION RATE: > 1 (Ethyl Ether = 1.0)

10. STABILITY AND REACTIVITY

STABILITY:

This product is stable

INCOMPATIBILITY (Material to Avoid):

None

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide, Volatile Hydrocarbon Vapours

HAZARDOUS POLYMERIZATION:

Can not occur

CONDITIONS TO AVOID:

High Heat, Sparks & Open Flames

11. ECOLOGICAL INFORMATION

No data given

12. DISPOSAL CONSIDERATIONS

- (1) Mechanical recovery
- (2) Flare-Off at safe location (Vapours)
- (3) Exhaust to atmosphere in safe location (No open flames)

OTHER DISPOSAL CONSIDERATIONS:

Disposal must comply with federal, state, and local disposal laws.

13. TRANSPORT INFORMATION

US DOT PROPER SHIPPING NAME: Petroleum Gases, Liquefied

US DOT HAZARD CLASS: 2.1

US DOT ID NUMBER: UN 1969

LABELED/PLACARDED Flammable Gas

14. REGULATORY INFORMATION

The ingredients listed in section 2 are reported/included in the U.S. TSCA inventory and Canadian domestics substance list.

The product is defined by OSHA in 29 CFR 1910.1200c as a flammable gas. Use of this product may require compliance with 29 CFR 1910.119, process safety management of highly hazardous chemicals.

15. OTHER INFORMATION

HMIS Classification:

Health: 1

Flammability: 4

Reactivity: 0

End of MSDS